



For Earth, For Life
Kubota

BX

KUBOTA DIESEL TRACTOR

BX Series

BX1880 / BX2380 / BX2680 / BX23S

Reliability. Comfort. Versatility.



* This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.

MEET THE BX SERIES



BX1880 18 ENGINE HP / 13.7 PTO HP

BX2380 23 ENGINE HP / 17.7 PTO HP

BX2680 25.5 ENGINE HP / 19.5 PTO HP

BX23S 23 ENGINE HP / 17.7 PTO HP

EVOLUTION OF THE BX SERIES

20 YEARS IN THE MAKING

In 2000, Kubota established the sub-compact diesel tractor market so that even first time operators can comfortably and efficiently perform a variety of gardening, landscaping, and general property maintenance tasks. This series not only maximizes its performance and versatility, but also includes operator comfort and styling improvements thus being the best BX Series Kubota has built to date.



BX00
2001

Kubota enters Australia and New Zealand with the sub-compact tractor category.



BX50 / BX24
2006

Further modern innovations and styling with the release of the BX50 Series.



BX70 / BX25D
2013

Started offering drive over mower decks and moved the location of the brake pedal to the left side for more comfort.



BX80 / BX23S
2017-Today

Introduced the Swift Tach Loader, allowing operators to remove the front end loader without getting off the drivers seat, as well as Swift Connect Backhoe, a single piece hood redesign and a third function valve kit.

2000

2020



BX30 / BX230
2004

Kubota expands the offering of the sub-compact tractors by introducing the BX30 Series and was one of the first tractor / loader / backhoe models.



BX60 / BX25
2009

BX60 introduces a higher horsepower model within the BX Series.



BX70 / BX25D-1
2015

Improved comfort by adding the reclining seat and foldable arm rests.

RELIABILITY

With a Kubota manufactured 3-cylinder diesel engine, HST transmission, all metal hood, fenders and chassis, the BX Series is Kubota engineered from front to rear making this a very reliable sub-compact tractor.

COMFORT

For a sub-compact tractor, the BX Series comfort is unmatched. With a flat operating station, tilt steering, ergonomic placement of levers and a deluxe seat, the BX Series prevents operator fatigue when working long hours on gardening, landscaping and property maintenance.

VERSATILITY

Kubota's versatile multi-purpose tractor offers four affordable models ranging from 18 to 25.5 HP to help you achieve your everyday tasks. This sub-compact tractor comes with an assortment of Performance Matched Land Pride implements such as a box blade, rotary cutter and post hole digger just to name a few. The BX Series line up also offers the BX23S, a dedicated tractor/loader/backhoe model to help you with all your digging jobs.



TABLE OF CONTENTS

Reliability	Comfort	Versatility	Implements / Accessories
P. 9	P. 13	P. 19	P. 27



RELIABILITY



RELIABILITY

KUBOTA DESIGNED, KUBOTA MANUFACTURED

Front to rear, the Kubota tractor is designed and built by Kubota for our Kubota customers. You won't find a "Kubota" re-branded tractor built by others, only Kubota quality through and through.



PERFORMANCE-MATCHED KUBOTA DIESEL ENGINE

All the BX Series tractors are powered by reliable diesel engines built by Kubota exclusively for the BX Series. The BX1880 and BX2380/BX23S come with 18 and 23 horsepower diesel engines, while the BX2680 packs a 25.5-horsepower diesel engine under the hood. All three engines are 3-cylinder workhorses that offer enough muscle to tackle even your toughest jobs.



EASY MAINTENANCE WITH ONE-PIECE METAL HOOD

Strong and durable, the BX Series' metal hood provides convenient access to the engine and protection ensuring that your BX tractor continues to look as good as it performs.



RELIABLE 2-RANGE HST TRANSMISSION

HST offers fast and smooth forward and reverse speed and direction changes via treadle foot pedals that leave your hands free for steering and implement control for maximum performance.



COMFORT



COMPACT SIZE

With an overall length similar to a standard garden tractor, BX-Series tractors are easy to drive and can work smoothly even in tight spaces. The BX-Series' compact size also means they're gentle on turf. But don't be fooled by their compact dimensions - these tractors are powerful and capable of handling a wide variety of chores and projects.

ROPS HEIGHT

The BX80-Series has a ROPS height of less than 7 feet (except BX23S) so you can drive the BX through most standard garage door openings without folding down the ROPS.

GROUND CLEARANCE

The BX Series provides plenty of ground clearance - 7.5 inches for the BX1880 and 8.4 inches for BX2380 / BX2680 / BX23S (without mid-mount mower) - to get you over rocks and other objects in your path.



SPACIOUS OPERATOR AREA

Operator comfort has been enhanced by a fully flat deck layout with the brake on the left side, providing more room for your feet. The new design also improves operability.

HIGH-BACK RECLINING DELUXE SEAT

A new deluxe seat helps keep the operator working comfortably and efficiently, even on the most demanding of tasks. The high-back reclining seat is fully adjustable and equipped with adjustable armrests. Soft cushioning supports the back and legs for optimum operator comfort. *(Excluding BX1880)*

TILT STEERING WHEEL

Repositioned for greater comfort and steering control, the BX80 Series steering wheel also tilts to accommodate operators of all shapes and sizes. *(Excluding BX1880)*

COMFORT



COMFORT



EASY TO READ INSTRUMENT PANEL
The new BX Series' instrument panel offers easy to read indicators for all of the vital information you need to keep your tractor running smoothly, safely, and efficiently. A single glance at the redesigned instrument panel tells you everything you need to know about the major functions and condition of your BX Series tractor. The large tachometer in the center features a convenient orange indicator for the optimum rpm range for loader/backhoe operations.



CRUISE CONTROL
Cruise control automatically maintains a constant speed, letting you take your foot off the forward pedal. It's the easy way to mow large areas or travel long distances. *(Optional on BX1880)*



ADDITIONAL FEATURES:

- Hydraulic Power Steering
- Left Side Brake Pedal
- Flat Floor for Increased Legroom
- Cup Holder
- Hand Rail
- 12V Socket & Storage Compartment
- Deluxe Lever Guide
- Foldable ROPS
- Tool Box *(Optional)*



VERSATILITY



VERSATILITY

PERFORMANCE MATCHED FRONT LOADERS - LA344 & LA340

Kubota's front loaders are built by Kubota and specifically designed to maximize the performance of the front loader and tractor. The Kubota-built LA344 is designed for the BX1880, BX2380, and the BX2680 while the LA340 is designed for the BX23S. They offer a large lifting capacity, perfect for landscaping or light utility work. The curved boom matches the hood design for a sleek and modern appearance and offers a better field of vision during front loader operations.

UNIQUE SWIFT-TACH DESIGN

Attaching and detaching Kubota's Swift-Tach front loader can be done in 4 easy steps all from the comfort of your seat. Simply follow the four steps listed below.



Step 1: Lift the loader boom and fully dump the bucket. Pull stand release lever to lower the front loader stand. Reposition the bucket so that it is in slightly dumped (20 degrees dump position) and lower the boom until the front axle is off the ground.



Step 2: Unlatch the loader latch levers to detach the front loader hooks.



Step 3: Use the loader lever to remove the loader frame from the mast. Turn off the engine and move the loader joystick lever to relieve the hydraulic pressure.



Step 4: Pull one lever to quickly and easily detach the hydraulic lines as a unit and store the coupler on the loader boom.



LOADER FEATURES

SIMULTANEOUSLY ATTACH & DETACH ALL FOUR HYDRAULIC LINES

The BX80 Series features a system for attaching and detaching all four hydraulic lines at the same time, making it even faster and easier to disconnect the front end loader. The no-spill type coupler help keep your tractor's frame clean and oil-free.

HOSE PROTECTION

The loader hoses are tucked inside the boom for greater protection and better operator visibility. (LA344)

3RD FUNCTION HYDRAULIC VALVE

The optional 3rd function hydraulic valves are used for front attachments that require hydraulic power such as grapples and 4in1 bucket.

Front Loader Specifications

Model Type		LA344		LA340
		BX1880	BX2380/BX2680	BX23S
Max Lift Height (to bucket pivot pin)	mm	1795	1804	1804
Dumping Clearance	mm	1316	1323	1323
Dumping Reach at Max. Lift Height	mm	642	646	646
Maximum Dump Angle	degrees	45		
Reach with Bucket on Ground	mm	1398	1392	1392
Bucket Rollback Angle	degrees	30	29	29
Digging Depth	mm	134	125	125
Bucket Width	mm	1219		
Lift Capacity (500mm fwd, max, height)	kg	231		231
Life Capacity (pivot pin, max, height)	kg	335		335
Loader with Standard Bucket Weight	kg	230		230
Breakout Force (500mm fwd)	N	4389		4389
Raising Time / Lowering Time (w/o load)	second	3.3 / 2.5		
Bucket Rollback Time / Dumping Time	second	2.3 / 2.7		



VERSATILITY



BX23S

From the moment you bring it home, the BX23S is ready to go to work loading, mowing, digging, and more. It comes with a performance-matched and fully integrated backhoe and front loader as standard equipment. Kubota's Swift-Connect and Swift-Tach systems let you quickly and easily attach the backhoe (Swift-Connect) and front loader (Swift-Tach). A heavy-duty reinforced frame provides the durability, stability, and strength to complete any tough task.

KUBOTA SWIFT-CONNECT

A simple lever operation is all it takes to quickly detach the backhoe from the BX23S, letting you drive away. To reattach, just back the BX23S into the backhoe and let the auto-lock mechanism secure them together.

REVERSIBLE SEAT

When it's time to switch from using the tractor or loader to using the backhoe, simply lift the reversible seat and rotate it to the back. The seat can also be adjusted forward and backward for optimal operator comfort.

BOOM & SWING CYLINDER CUSHION VALVES

Standard on the BX23S, an integrated cushion valve ensures smooth movement both horizontally and vertically, minimizing the shock that's transmitted to the operator when the backhoe arm hits its range limits.

NO-SPILL COUPLER

The backhoe uses the same No-Spill coupler system as the front loader to help keep your backhoe clean and oil-free.

WIDE VIEW

The benefit of tucking the hydraulic hoses inside the backhoe boom provides greater protection for the hoses and greater visibility for the operator.



MECHANICAL THUMB

(Optional)

A positionable mechanical thumb gives the BX23S the ability to grasp and move logs, landscaping materials, and other items with ease, greatly expanding the types of jobs you can do around your property.




BX23S** Backhoe Specifications		
Model	BT603	
Bucket Cylinder Digging Force	N	8610
Dipperstick Cylinder Digging Force	N	5209
Boom Swing Mechanism	One Cylinder	
Backhoe Weight (with 12" bucket)	kg	275
Transport Height	mm	1719
Loading Height	mm	1533
Digging Depth	mm	1842
Swing Pivot to Rear Axle Center Line	mm	726
Reach from Swing Pivot	mm	2612
Bucket Rotation	degrees	180
Swing Arc	degrees	140
Angle of Departure	degrees	20.1

*SAE J1995

**The loader and backhoe come standard on the BX23S model.

MID-MOUNT MOWER

The versatile BX Series tractors are easy to drive and maneuver, letting you take on the most challenging mowing jobs with confidence and efficiency. BX Series tractors maneuver easily between trees and other tight places in the yard. Their compact size also means they're gentle on turf. The Easy-Over mid-mount mower deck is quick to attach and detach, and is available in two sizes—54" and 60"—to match your specific mowing needs.



STANDARD DECK

This 3-blade mower offers a wide cutting area, allowing you to cut more grass in a single pass. Choose a 54" deck for the BX1880 or a 54" / 60" deck for the BX2380 / BX2680 / BX23S.



MOWING-HEIGHT ADJUSTMENT DIAL

A simple twist of the dial adjusts the mower height in 1/4" increments to your desired cutting level.



DURABLE SHAFT DRIVE

The BX Series' shaft drive delivers power smoothly from the mid-PTO to the mid-mount mower. Unlike belt drives, there is no slippage and maintenance is minimal.



HIGH CLEARANCE

With 6 inches of clearance, the BX Series tractors easily travel over uneven ground and protruding obstacles.



EASY ATTACH/DETACH

The mower can be attached and detached quickly and easily—saving you time and effort.

Mid-Mount Mower Specifications			
		RCK54-23BX	RCK60B-23BX
Model		BX1880 BX2380 BX2680 BX23S	BX2380 BX2680 BX23S
Type		Side Discharge	
Number of Blades		3	
Mounting Method		Suspended-Linkage	Self Balance
Cutting Width	in. (mm)	54 (1372)	60 (1524)
Cutting Height	in. (mm)	1.0 - 4.0 (25 - 102)	
Adjustment of Cutting Height		1/4" Dial Gauge	
Weight	kg	95	115
Ground Clearance in Transport Position	in. (mm)	6.0 (152)	

Easy-Over Mower Specifications			
		RCK54D-26BX-1	RCK60D-26BX-1
BX2380 BX2680	BX23S	BX2380 BX2680	BX23S
Side Discharge			
3			
Drive Over Suspended-Linkage			
54 (1372)		60 (1524)	
1.0 - 4.0 (25 - 102)			
1/4" Dial Gauge			
122	117	134	129
6.0 (152)			



VERSATILITY

BUILT TO SUCCEED

From digging and scraping to mowing and plowing, there's a BX Series implement that can do it faster, easier, and more efficiently. Also available is the Land Pride 3-point quick hitch which will allow for easy attaching and detaching of approved 3-point implements, often without ever having to get off the tractor!



MID-MOUNT MOWER



GROOMING MOWER



ROTARY CUTTER



QUICK HITCH



GRAPPLE



ROTARY TILLER



GRADING SCRAPER



POST HOLE DIGGER



4-IN-1 BUCKET



DISC HARROW



REAR BLADE



BOX SCRAPER

TYRES

INDUSTRIAL TYRE
(BX2380, BX2680,
BX23S only)

TURF TYRE
(BX1880, BX2380,
BX2680 only)

BAR TYRE
(BX1880, BX2380,
BX2680 only)



TYRE OPTIONS

Kubota's BX Series offers a variety of tyre tread types. Turf tyres are designed for minimal ground disruption, and industrial tyres are designed for a more every day use style tread.



Specifications

Model			BX1880	BX2380	BX2680	BX23S
Engine	Liquid-cooled, 3-cylinder diesel					
Type						
Model			Kubota D722	Kubota D902	Kubota D1005	Kubota D902
Engine gross HP at 3200 rpm ^{*1}	HP (kW)		18 (13.4)	23 (17.1)	25.5 (19)	23 (17.1)
PTO horsepower at 3200 rpm	HP (kW)		13.7 (10.2)	17.7 (13.2)	19.5 (14.5)	17.7 (13.2)
Displacement	cu.in. (cc)		43.9 (719)	54.8 (898)	61.1 (1001)	54.8 (898)
Fuel tank capacity	L		25			
Drive train	HST, High-Low gear shift (2 forward / reverse)					
Transmission						
Drive method	4WD					
Brakes	Wet disc					
PTO	Live independent PTO (with hydraulic clutch)					
Rear	STD (540rpm)					
Mid	STD (2500rpm)					
Hydraulics	23.5					
Pump output	L/min.					
3-point hitch	SAE Category I				Optional	
Lift capacity @ 24" behind pin	kg		310			
Steering	Hydrostatic Power Steering					
Tyre size						
Front	Turf/Bar/Industrial		16x7.5-8 / 16x7.5-8 / N.A.	18x8.5-10 / 18x8.5-10 / 18x8.5-10		18x8.5-10 / N.A. / 18x8.5-10
Rear	Turf/Bar/Industrial		24x12-12 / 24x12-12 / N.A.	26x12-12 / 26x12-12 / 26x12-12		26x12-12 / N.A. / 26x12-12
Traveling speeds at rated engine rpm (Turf)	Forward	km/h	0-12.5		0-13.5	
	Reverse	km/h	0-9.5		0-10.5	
Dimensions			2425			2515 w/ Front guard
Length with 3-point hitch	mm					
Width	mm		1120	1145		
Height with ROPS	mm		2080	2110	2190	
Wheelbase	mm		1400			
Ground clearance (front axle)	mm		193	213		
Tread	Front	mm	930			
	Rear	mm	820			
Turning radius (w/o brake)	m		2.3			
Tractor weight (w/ROPS)	kg		606	650	670	712 ^{*2}

*1 Manufacturer's estimates *2 w/Front guard, w/control valve assy

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.



Kubota Australia Pty Ltd

25-29 Permas Way, Truganina VIC, 3029 Australia

Freecall: 1800-334-653

Email: sales@kubota.com.au

www.kubota.com.au

Kubota New Zealand Limited

433 Rangitikei Street, Cloverlea, Palmerston North, 4412

Freecall: 0800-582-682

Email: sales@kubota.co.nz

www.kubota.co.nz