

CP30 SERIES COLD PLANERS

Available for: SSV65 | SSV75 | SVL65 | SVL75 | SVL97

DEMOLITION



KEY FEATURES

- Independent RH/LH skid shoe control
- Hydraulic tilt, depth, and sideshift integrated into multi-function grips of the SSV/SVL
- Optional water system
- Removable cutting teeth
- 3 Line set up (pressure, return, and case drain)

Road contractors, municipalities, and rental yards will find this tool ideal for milling asphalt, cutting utility trenches, and pothole/shoulder repairs.



The CP30 Series features a 6" cutting depth, 5/8" drum wall and 2-1/2" tooth standoff for efficient milling.

| | CP3012LF | CP3016LF | CP3018 | CP3024 | CP3030 | CP3040 | CP3048 |
|----------------------------------|---------------------|-------------------|---------------------|-------------------|---------------------|---------------------|---------------------|
| Cutting Width (cm) | 12" (31) | 16" (41) | 18" (41) | 24" (61) | 30" (76) | 40" (102) | 48" (122) |
| Cutting Depth (cm) | 0 - 5 (0 - 13) | | 0 - 6 (0 - 15) | | | | |
| Weight (kg) | 1190 lbs (540) | 1360 lbs (617) | 1635 lbs (741) | 1805 lbs (819) | 1895 lbs (860) | 2215 lbs (1005) | 2410 lbs (1093) |
| Number of Picks | 30 | 38 | 46 | 56 | 66 | 82 | 94 |
| Min. Hydraulic Flow (Lpm) | 15 gpm (56.8) | | 24 gpm (91) | 27 gpm (102) | 30 gpm (114) | | |
| Max. Hydraulic Flow (Lpm) | 25 gpm (94.6) | | 42 gpm (159) | | | | |
| Min. Pressure (MPa) | 2,000 psi (1.38) | | 2,000 psi (1.72) | | 2,500 psi (1.72) | 3,000 psi (2.07) | 3,500 psi (2.41) |
| Max. Pressure (MPa) | 3,500 psi (24) | | 5,000 psi (34) | | | | |
| Tilt Capability | +/- 15° | | +/- 15° | +/- 13° | +/- 10° | +/- 8° | +/- 6° |
| Sideshift Travel (cm) | | | | 26" (66) | | | |
| Wall Clearance (cm) | N/A | | 4" (10 cm) | | | | |