

# HB SERIES HOPPER BROOMS

Available for: SSV65 | SSV75 | SVL65 | SVL75 | SVL97

MATERIAL HANDLING



## KEY FEATURES

- Heavy-duty bucket design - 3/16" shell
- Bucket tapered front to back to hold material in
- 26" Replaceable brush
- Tool-less height adjustment
- Heavy-duty metal top with bump protection

This large, tapered, heavy-duty collection bucket offers multiple broom configurations making it the perfect construction site clean-up tool for contractors & rental yards.



The optional gutter broom adds 12" to the cleaning width and makes it easier to clean curbs and alongside buildings. Broom height is adjusted with a simple pin - no tools needed.

The heavy-duty bucket offers a 3/16" shell, and is tapered front to back to help hold in material. The heavy-duty metal top offers bump protection to take on the day-to-day use of construction sites. Optional dust suppression kit is available.



|  |                                       | HB74   | HB84                     |
|--|---------------------------------------|--|--------------------------|
| Weight of Base Unit w/Brush (kg)       |                                       | 1,252 lbs (568)  | 1,369 lbs (621)          |
| Optional Weights                       | Gutter Broom (kg)                     | 101 lbs (46)   | 101 lbs (46)             |
|  | Dust Suppression (kg)                 | 194 lbs (88)   | 206 lbs (93)             |
|  | Dust Suppression w/ Gutter Broom (kg) | 197 lbs (86)   | 210 lbs (95)             |
| Overall Width (m)                      |                                       | 82" (2.08)   | 92" (2.34)               |
| Overall Height (m)                     |                                       | 46" (1.17)   | 46" (1.17)               |
| Wafers                                 | Poly Broom                            | 36 Poly Wafers   | 41 Poly Wafers           |
|  | Wire Broom                            | 36 Wire Wafers   | 41 Wire Wafers           |
|  | Combination Broom                     | 18 Poly & 18 Wire Wafers   | 21 Poly & 20 Wire Wafers |
| Sweeping Width (m)                     |                                       | 74" (1.88)   | 84" (2.13)               |
| Sweeping Width w/ Gutter Broom (m)     |                                       | 86" (2.18)   | 96" (2.44)               |
| Broom Diameter (cm)                    |                                       | 26" (66)   |                          |
| Broom Rotor Shaft                      | w/o Gutter Broom w/ Gutter Broom      | Quick change broom core with no hydraulic hose disconnect in changeover. Quick change broom core with return to sump hydraulic hose disconnect only. |                          |
| Hydraulic gpm Range (lpm)              |                                       | 12-25 gpm (45-95)  |                          |
| Min. Hydraulic Flow Required (lpm/mPa) |                                       | 12 gpm (45) @ 2000 psi (13.8)  |                          |
| Max. Hydraulic Pressure Rating (mPa)   |                                       | 3500 psi (24.1)  |                          |
| Broom Speed Range                      |                                       | 100-230 rpm  |                          |
| Hydraulic Rotor Drive Motor            |                                       | Single motor drive standard  |                          |
| Bucket Shell Thickness (mm)            |                                       | 3/16" (4.8)  |                          |
| Bolt-on Cutting Edge (cm)              |                                       | Standard 5/8" x 8" (1.6x20.3)  |                          |
| Broom Hood Thickness (mm)              |                                       | 12 ga. Sheet metal (2.6)   |                          |
| Optional Water Tank Capacity (L)       |                                       | 25 gal. (95)   |                          |