

SC25 SERIES SKID CUTTERS

Available for: SSV65 | SSV75 | SVL65 | SVL75 | SVL97

CUTTERS



KEY FEATURES

- 2" Diameter cut capacity
- 1-1/2" - 18" Cutting height; infinitely variable
- 10 Gauge steel deck; 1/4" side skirt

Ideal for restricted areas under fences, in and around boxed in corner sections of corrals and out buildings, vineyards, nursery rows, wooded lots, and approaches to ditches and waterways.

Center mount with offset hitch option allows operator to offset 8-1/2" to the right to cut close to obstacles.



Optional front gauge wheel provides easy operation and handling over uneven terrain. Laminated tire can't go flat.



		SC2560	SC2572
Cutter Weight (kg) w/o Skid Shoes, Gauge Wheel, & Protective Door		893 lbs (405)	1,084 lbs (491)
Gauge Wheel Weight (kg) Optional		114 lbs (51)	
Cutting Width (m)		60" (1.52)	72" (1.83)
Overall Width (m)		65-1/2" (1.66)	78" (1.98)
Overall Length (m)		73" (1.85)	91" (2.31)
Cutting Capacity (cm)		2" (5.1) Diameter	
Drive Motor	Medium Volume (lpm)	18-23 gpm (68-87) flow	
	High Volume (lpm)	24-30 gpm (90.8-113.6) flow	
Deck Thickness (mm)		10 Ga. (3.4)	
Side Skirt Construction (mm)		1/4" (6)	
Skid Shoes Construction (cm) Optional		Standard-duty skid shoes: 1/2" x 2" (6 x 5.1) steel Heavy-duty skid shoes: 3/8" x 3" (1 x 7.6) steel	
Blade Carrier		Heavy-duty round pan stump jumper	
Blade Size (cm)		1/2" x 4" (1.3 x 10.2) updraft	
Blade Tip Speed	18-23 gpm Motor (mps/lpm) at 23 gpm (87.1)	13,455 fpm (68.3) at 23 gpm (87.1)	14,940 fpm (75.9) at 23 gpm (87.1)
	24-30 gpm Motor (mps/lpm) at 30 gpm (113.6)	13,769 fpm (69.9) at 30 gpm (113.6)	16,523 fpm (83.9) at 30 gpm (113.6)
Height Adjustment Safety Chain		Standard	

**INTELL
ATTACH**
COMPATIBLE